

I Full HD 2MP, H.265 X36 Auto Focus Zoom 지능형 IP Box Camera



iSTA-C200N

Key Features

- 1/1.9" Sony CMOS Image Sensor
- H.265 / H.264 / MJPEG 다중 압축방식 지원
- 최대 줌 Optical 36x Zoom / Digital 32x Zoom
- 렌즈 F= 6mm ~ 216mm / F1.5(wide) ~ F4.8(tele)
- 최저조도 Color : 0.0375 Lux / BW : 0.002 Lux
- Real-Time True WDR
- Digital Image Stabilizer
- Defog Function
- ONVIF Profile-S
- 1 x Sensor-In / 1 x Alarm-Out
- RS-485 통신 지원
- TTA인증 : 공공기관용 IP카메라 보안 성능품질 Ver.1



CAMERA PART

| | |
|----------------------|--|
| 촬상소자 | 1/1.9" Sony CMOS Sensor |
| 유효화소수 | 1937(H) x 1097(V)=2.12M Pixels |
| 해상도 | 1920 x 1080p |
| 렌즈 | F= 6mm ~ 216mm / F1.5(wide) ~ F4.8(tele) |
| 화각(D/H/V) | D : 63.31°(W)~2.44°(T) / H : 56.5°(W)~2.12°(T) / V : 33.63°(W)~1.19°(T) |
| 줌 배율 | 광학 36배 줌 & 디지털 32배 줌 |
| 최저조도 | Color : 0.0375 Lux / BW : 0.002 Lux |
| Day & Night | Auto / Day / Night |
| White Balance | Auto / One Push / Manual / Indoor / Outdoor |
| 역광보정(WDR/BLC) | Real-Time True WDR, Off / WDR / BLC / HLC |
| Function | Digital Image Stabilizer / Defog Function |
| DNR | Auto / Off / Low / Middle / High |
| Digital Slow Shutter | Off / 2x / 4x |
| 영상 압축 방식 | H.265 / H.264 / MJPEG |
| 영상 스트리밍 | Primary : H.264 Secondary x3 : H.264 / MJPEG |
| 접속 | Ethernet 10/100/1000base-T (RJ-45) |
| IP | IPv4 / IPv6 |
| 네트워크 프로토콜 | TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL, DHCP, PPPoE, FTP, SMTP, ICMP, IGMP, SNMPv1/v2/v3(MIB-2), ARP, DNS, DDNS |
| ONVIF | 지원 |
| 주변 장치 | 1 x Sensor-In (NO) 1 x Alarm-Out (NO) 1 x RS-485 port |
| 전원 | DC12V/1.5A, PoE(Power over Ethernet) : 802.3af |
| 동작온도 | -10°C ~ 60°C / Lens than 80% RH |
| 규격 | 76(W) x 225(L) x 66(H)mm |
| 무게 | 1.0kg |